PROCESS CONTROL: 0 to 24 mA

MODEL	BITS #	D/A's #	Power Supply Requirements +Vs +Volts	+Is + mA	Is in sdown uA	Output Voltage +5Vdd	+15Vdd	Output Current mA	Settling Time msec to 1/2 LSB +5V	+15V	Accuracy or Linearity Lsb's +25C	Tmax	Differential Linearity Lsb's +25C	Tmax	Total FS Error Lsb's +25C	Lsb/C	Zero Error Lsb's +25C	Lsb/C	Voltage Reference Int	Ext	I/O Input Buffers	C L E A R	' B A K	+70C	-25 85	-40 85	-55 125	# of Pins	Price 100's
AD420 (Output Ranges 4 to 20 mA, or 0 to 20 mA, or 0 to 25 mA.)																													
AD420 (LOCALLY POWERED)																													
AD420-32	16	-24/32	5			0 to +5V	4 to 20mA	3000	na	3	8		1		98	3	33	3	+5V		S3.3Mhz	Y	Y				X	20	$11.50
AD421 (Output Ranges 4 to 20 mA), w/ON CHIP +3 or +3.3 or +5V Regulator																													
AD421 (LOOP POWERED)																													
AD421	16	+3/5	0.5			0 to +5V	4 to 20mA	3000	8	na	7		1		131	1.5	66	3	+1.25V & 2.5V		S3.3Mhz	Y	Y				X	16	$8.00
AD422 (Output Ranges 4 to 20 mA), w/ON CHIP +3 or +3.3 or +5V Regulator																													
AD422 (LOOP POWERED With Intergral HART Modem)																													
AD422	16	+3/5	0.75			0 to +5V	4 to 20mA	8000	8	na	7		1		131	1.5	66	3	+1.25V & 2.5V		S3.3Mhz	Y	Y				X	16	$12.25